



Convenience Stores / Grocery Stores



Tobacco Stores / Liquor Stores



Cafeterias / Concessions



Table Service and Quick Service Restaurants



Hardware, Paint or General Retail Stores



**High Performance POS Touch Terminal
Designed For Optimum Performance and
Dependability**



The Histone HK950S Intel® Core™ Skylake-S 6th Generation CPU provides higher performance and lower power consumption. The HK950S true flat touch terminal includes both projected capacitive touch and a solid state drive for optimum performance and reliability in harsh retail and food service environments.

- 6th Generation Intel Core™ i5 6500TE Processor
- RAID Support (HK950SQ)
- Solid State Drive Improves Performance and Reliability
- 15" True-Flat Screen
- Projected Capacitive Touch (PCT)
- Vivid LED Backlight
- Die-Cast Aluminum Housing
- Power Supply Can Be Placed Inside the Base
- Suitable For Demanding Application Software



HK950S Touch Screen Terminal



Sleek Cabinet Design – One Convenient USB Port (V2.0) on the Left Side



Optional Integrated VFD Customer Display



Optional Integrated 10" or 15" (Shown) Rear LCD Customer Display



Cable Management Keeps Cords Hidden and Organized Neatly Tuck the Power Supply Inside the Cabinet

Options and Upgrades

Configure your system with these easy to add options:

- Integrated VFD Customer Display – 2 Lines x 20 Characters
- Integrated 15" or 10" LCD Customer Displays
- Encrypting Triple Track Card Reader
- Augusta Reader and Bracket
- Integrated Fingerprint Reader
- WiFi Module
- Wall Mount Bracket with Standard VESA Configuration

Applications

The attractive, powerful HK950S touch terminal is ideal for harsh environments like pizza, quick service restaurants, bakeries, industrial shop floors, and many more:

- Airline Counters
- Automotive Services
- Convenience Stores
- Digital Signage
- Dry Cleaners
- Financial/Banking
- Food & Drug Stores
- Gaming
- Hospitality
- Hotel Front Desk
- Interactive Workstations
- Kiosks
- Kitchen Video
- Medical
- Message Stations
- Point of Sale
- Quick Service
- Rental Car
- Rental Stores
- Retail Scanning
- Self Service
- Streaming Video
- Table Service
- Training
- Unattended Workstations


Connectivity

Ports are located below the touch screen. Cable management keeps cables hidden and organized. Four RJ48-DB9M adaptors are included.

- | | |
|----------------------------------|--------------------------------|
| A DC Out (12V) – Rear LCD | H LAN |
| B DC In (24V) | I COM1 (RJ48) |
| C VGA | J COM2 (RJ48) – Powered |
| D HDMI | K COM3 (RJ48) – Powered |
| E Two USB (V3.0) | L COM4 (RJ48) – VFD |
| F Two USB (V3.0) | M Audio |
| G Cash Drawer (RJ11) | |

Specifications

	HK950SH	HK950SQ
Processor:	Intel Core i5 6500TE CPU	
Cores / Threads:	Quad Core / 4 Threads	
Cache Memory:	6MB Smart Cache	
Display LCD:	True Flat 15" LCD with LED Backlighting	
Resolution:	1024 x 768	
Brightness:	Adjustable Up to 400 cd/m ²	
Integrated Speakers:	Two Integrated 2 Watt Speakers	
Chipset (PCH):	CPU Integrated	
Touch:	Projected Capacitive Touch (PCT)	
MCR:	Integrated USB Interface Triple Track MCR	
Mass Storage Device:	128GB 2.5" Solid State Drive	
RAM Memory (1 Slot):	8GB SODIMM DDR4	16GB SODIMM DDR4
	Expandable To 16GB	
RAID Support:	No	Yes
Graphics Video Memory:	Intel HD Graphics 530 / 64GB Maximum	
Tilt Adjustment:	0° ~ 45° (Adjustable)	
Serial Ports:	COM1 COM2 / COM3 / COM4 (0V/5V/12V – Selectable by BIOS)	
USB Ports:	Four V3.0 / Two V2.0	
Cash Drawer Port:	RJ12 (24V) – Maximum 2 Drawers – Supports Open/Close	
HDMI Port:	One HDMI	
LAN Port:	RJ45 100M/1000M Gigabit LAN	
VGA Port:	One DB15F Display Port For Second LCD	
Audio Port:	One Line-Out	
Mic Port:	Not Applicable	
Power Supply:	90W, 24V/3.75A External Power Adaptor 100-240V 50-60Hz	
Current / Power Usage:	0.39A / 42W (110V Idle Environment) – 0.50A / 54W with Rear LCD	
Environment – Operating:	32° F to 104° F / 40% to 90% RH Non-Condensing	
Storage:	-4° F to 140° F / 10% to 90% RH Non-Condensing	
Compatible O/S:	Windows 10 Pro / Windows 10 IoT 2019 Value	
Dim. / Weight – Overall:	16"W x 11-1/8"D x 13-5/8"H	18.2 lbs.
Shipping Carton:	21"L x 15"W x 20"H	25.1 lbs.
Safety and EMI:	FCC / CE	



All product and company names are trademarks, service marks or registered trademarks of their respective owners. All features and specifications are subject to change without notice.

© 2022, Printed in U.S.A.

Lit-358 **HiStone**