

Hisense

HM388

8" Point of Sale Tablet



8" Tablet for Point of Sale Applications

The Hisense HM388 Windows tablet can be used as a cost effective hand held terminal for line busting, by waitresses for table side order entry and by store clerks for assisting customers on the floor. The included docking / charging station includes a serial and USB ports that can be used to control a variety of peripherals when the tablet is used as a budget-friendly stationary workstation.

The 8 inch, bezel-free and wide screen display is designed with Projected Capacitive (PCAP) touch technology that helps to extend the operating life and allow multi-touch gesture control. Use the ports in the included docking station to connect to a wide range of peripheral devices.

- 8" Wide Screen
- Bezel-Free, PCAP Multi-Touch Screen
- Standard Integrated Card Reader
- Standard Docking Station Includes I/O Expansion Ports



HM388 – 8" Point of Sale Tablet



Stylish, Space-Saving Tablet Includes Docking Station



Integrated Card Reader Standard



Standard Docking Station Includes I/O Expansion Ports

Features

- Front and Rear Cameras
- Integrated Card Reader
- 0.8 Watt Speaker
- LED Indicator
- Built-In Microphone Provides Sound Input While Making Web-Calls
- Capture a Front View Picture or Record Videos
- HM388 Tablet Includes a Built-In Battery
- Docking Station Includes Power Adaptor and Cord
- Compatible with Popular Standard Applications

Specifications

		HM388
Processor:		Cherrytrail Z8350
Operating System:		Windows 10 IoT Enterprise LTSC
Display:		8" TFT LCD (LED Back-Light)
Resolution:		1280 x 800
Brightness:		300 cd/m2
Touch Panel:		True-Flat Projected Capacitive Touch
Memory:		2GB RAM
Storage:		32GB eMMC
Camera –	Rear:	5 Megapixel Camera
	Front:	0.3 Megapixel Camera
Wireless –	Wi-Fi:	WiFi802.11 b/g/n 2.4GHz
	Bluetooth:	Integrated Bluetooth V4.0
Speaker:		8 Ohm, 1 Watt Speaker
Audio:		3.5mm Socket
MCR:		Standard Integrated Triple Track Card Reader
NFC:		Supports MIFARE one and MIFARE CPU Card
Battery –	Type:	4000mAh (3.8V)
	Life:	4 Hours
I/O Interface:		Micro-SD Slot / Micro-USB / Audio / Micro HDMI 1.4a
Tablet Connector:		7 Pin Pogo Style Connector
Docking Station –	I/O:	Three USB 2.0 / COM (RJ48)
	DC Input:	One DC Jack (5V)
Power Supply:		5V / 3A External Power Adaptor 100-240V 50/60Hz
Temperature –	Operating:	32° F to 104° F (0° C to 40° C)
	Storage:	-4° F to 149° F (-20° C to 65° C)
Humidity –	Operating:	20% to 90% RH (Non-Condensing)
	Storage:	20% to 93% RH (Non-Condensing)
Dimensions –	Tablet:	9"W x 4-13/16"H x 1/2"D
	Tablet/Docking Station:	9"W x 8"H x 4-1/2"D
Safety and EMI:		FCC Class-B / CE Class-B / RoHS

Camera | Charging Indicator



Micro SD Card Slot

Speaker | Volume – | Volume + | Power | Camera



MCR | DC Jack | COM (RJ48) | USB | HDMI | Micro USB | DC Jack | Audio