

SNBC

Extraordinary
Value!

BTP-P35

Mobile POS Printer



The BTP-P35 is a small and lightweight mobile receipt printer... a prudent choice for any mobile receipt printing application where you need fast, on-demand printing with speeds up to 102mm (4") inches per second. The BTP-P35 also features a long-life Lithium-ion battery. The optional integrated magnetic card reader (factory option) allows credit cards to be processed immediately at the point of transaction, increasing customers' sense of security since the credit card does not leave their sight.

- Compact, Mobile Printer with OLED Display
- USB+Bluetooth and USB+WiFi Interfaces
- SDK Available for Apple iOS™ and/or Android™ Compatibility
- Includes 2600mAh Large Capacity Lithium-ion Battery
- Meets IP54 Standard for Exposure to Water and Dust
- Withstands Drop of 5 Feet (1.5 Meters)



BTP-P35 Mobile POS Printer



Compatible With Smart Devices



Water and Dust Resistance



Card Reader Option

Features

- Compact, Mobile Printer with OLED Display
- USB+Bluetooth and USB+WiFi Interfaces
- SDK Available for Apple iOS™ and/or Android™ Compatibility
- Includes 2600mAh Large Capacity Lithium-ion Battery
- Meets IP54 Standard for Exposure to Water and Dust
- Withstands Drop of 5 Feet (1.5 Meters)
- Includes Starter Paper Roll, Battery, External Power Adaptor and Cord, User's Manual and Belt Clip

Applications

- Customer Service Center
- Deliveries
- Government
- Hospitality
- Insurance
- Logistic
- Mobile Printing
- Parking
- Retail
- Ticketing

Optional Devices / Upgrades

Modify or upgrade your printer with these easy-to-add options:

- Battery Charger (Single)
- Vehicle Charger
- Shoulder Strap
- Protection Case



On Screen Programming Simplifies Setup

Specifications

Print Method:	Direct Thermal
Resolution:	203 DPI
Print Width:	72mm (2.8")
Print Speed:	102mm (4") Maximum
Memory –	Flash: 4MB
	RAM: 64MB
Interpreter:	ESC/POS™
Interface –	Standard: USB+WiFi or USB+Bluetooth
Drivers –	32 Bit: Windows® 10 / 8.1 / 8 / 7 / Server 2012 / Server 2008 / Server 2003 / XP Prof. / XP Home / 2000 Server / 2000 Prof. / Vista / POSReady 2009
	64 Bit: Windows® 10 / 8.1 / 8 / 7 / Server 2012 / Server 2008 / Server 2003 / XP / Vista
Bar Code –	1D: CODE39 / CODE93 / CODE128 / CODABAR / UPCA / UPCE / JAN8 (EAN8) / JAN13 (EAN13) / ITF
	2D: PDF417 / QR Code / Maxicode / GS1
Fonts:	Standard Font A (12x24) / Standard Font B (9x17) / User Defined Character / Kanji (24 x 24) / English (ASCII) / American / English / Japanese / Korean (Option) / Can Download Defined Character fo FLASH or RAM
Paper –	Type: Continuous Paper / Black Mark Paper
	Thickness: 0.06 ~ 0.16mm
	Width: 60 or 80mm (2.4" or 3.1") Maximum
	Inside Diameter: 12.5mm (1/2")
	Outside Diameter: 50mm (2") Maximum
	Paper Cutting Method: Tear-Off
Display:	OLED Screen
Alarm:	Buzzer
Battery –	Capacity: 7.4V Li-ion / 2600mAh / Removable / Rechargeable Lithium Polymer Battery
	Charging Time: 3.5 Hours
Power Supply –	Input: AC 100 ~ 240V, 50/60 Hz Adapter Included
	Output: 12VDC±5% / 2A
Temperature –	Operating: -4° ~ 122°F (-20° ~ 50°C)
	Storage: -4° ~ 140°F (-20° ~ 60°C)
Humidity –	Operating: 10% ~ 90% RH (Non-Condensing)
	Storage: 10% ~ 90% RH (Non-Condensing)
Dimensions / Weight –	Unit: 2-3/8"W x 4-3/8"D x 6-1/2"H / 1.20 lbs. (Incl. Battery)
	Shipping Carton: 12-1/4"L x 9"W x 4"H / 2.46 lbs.
Safety and EMI:	CE / CB / FCC / UL