

SAM4S

SPT-4740



Bars / Ice Cream Parlors / Coffee Shops



Gift Shops / Dollar Stores



Pizza / Table Service / Quick Service / Liquor Stores



Cafeterias / Delis

Best-in-Class Value Fanless POS Touch Screen Terminal



The high performance SAM4S SPT-4740 touch screen terminal with a **dual-core fanless** CPU is designed to reliably and efficiently power demanding POS software applications in hospitality, quick service, grocery, and retail markets.

- 15" LCD with ELO® 5-Wire Resistive Touch
- Intel Celeron 1037U Dual Core 1.8GHz Fanless Processor
- 4GB RAM
- 5-Wire Resistive Touch
- Vivid LED Backlight for Reliability and Energy Savings
- Compatible with Popular Application Software
- Easily Wall Mountable
- Variety of Optional Integrated Customer Displays
- Connection Panel Allows Cables to Be Hidden and Routed Neatly Through the Base and Out the Rear of the Terminal



SPT-4740 Touch Screen Terminal



Optional Integrated 15" Rear LCD Customer Display



Optional Integrated 7" Rear LCD Customer Display



Optional Integrated VFD Customer Display



Tool-Free Access to Hard Disk Drive and RAM Optimizes Serviceability

Options and Upgrades

Configure your system with these easy to add options:

- Integrated VFD Customer Display
 - 2 Lines x 20 Characters
- Integrated 15", 9.7" or 7" LCD Customer Displays
- Encrypting Triple Track Card Reader
- Integrated Triple Track Card Reader with Integrated Fingerprint Reader
- Augusta Reader Bracket
- Solid State Drive
- WiFi Module
- Wall Mount Bracket with Standard VESA Configuration

Applications

The attractive, powerful SPT-4740 fanless terminal is ideal for harsh environments like pizza, quick service restaurants, bakeries and industrial shop floors and for processor intensive applications including table service, retail scanning and many more:


- Airline Counters
- Automotive Services
- Convenience Stores
- Digital Signage
- Dry Cleaners
- Financial/Banking
- Food & Drug Stores
- Gaming
- Hospitality
- Hotel Front Desk
- Interactive Workstations
- Kiosks
- Kitchen Video
- Medical
- Message Stations
- Point of Sale
- Quick Service
- Rental Car
- Rental Stores
- Retail Scanning
- Self Service
- Streaming Video
- Table Service
- Training
- Unattended Workstations

Connectivity

- A** Drawer Voltage Selector Switch
- B** Cash Drawer
- C** Parallel
- D** Line-Out
- E** Mic-In
- F** Line-In
- G** USB (2)
- H** LAN
- I** COM1 (Powered)
- J** COM2 (Powered)
- K** USB (2)
- L** COM3 (Powered)
- M** VGA
- N** COM4 (Powered)
- O** DC Out (For Rear LCD)
- P** DC In (Power)

Specifications

Processor:	Intel Celeron 1037U 1.8GHz Fanless
Cores / Threads	Dual Core / 2 Threads
Cache Memory:	2MB
Bus Speed:	5 GT/s (Giga Transfers per Second)
Display LCD:	Bezeled 15" LCD with LED Backlighting
Resolution:	1024 x 768
Brightness:	Adjustable Up to 250 cd/m ²
Integrated Speakers:	Integrated 2 Watt Speakers
Chipset (PCH):	NM70
Touch – Panel:	5-Wire Resistive Touch
Reliability:	Over 36 Million Touches
MCR:	Integrated USB Interface Triple Track MCR
Hard Drive:	2.5" With SATA Interface
RAM Memory (2 Slots):	4GB SODIMM DDR3 (1600MHz)
Video Memory:	Shared System Memory Up To 512MB
Serial Ports:	COM1, COM2, COM4 = DB9M With Pin 9 Voltage (0V/+5V/+12V) Selectable By BIOS / COM3 = RJ45 Pin 1 Voltage (0V/+5V/+12V) Selectable By Jumper COM5 for Touchscreen / COM6 = RJ45 for Customer VFD
Parallel Port:	One DB25F
USB Ports:	6 V2.0 (2 Left Side / 4 Bottom)
Cash Drawer Port:	RJ12, 12V or 24V Selectable By Switch (Maximum 2 Drawers – Supports Drawer Compulsion)
LAN Port:	RJ45 10/100/1000 Base-T (Giga LAN) RealTek RTL8111E
VGA Port:	One DB15F Display Port For Second LCD (Maximum Resolution 2048 x 1536)
Audio Port:	One Line-In / One Line-Out
Mic Port:	One Mic-In
Power Supply:	60W, 12V/5A External Power Adaptor 100-240V 50-60Hz
Current / Power Usage:	0.25A / 27W
Environment:	32° F to 104° F / 0% to 90% RH Non-Condensing
Compatible O/S:	POSReady 7 / Windows 7 Professional / Windows 10 Professional / Windows 10 IoT Enterprise 2016 LTSP
Dimen. / Weight – Base:	11"W x 7-3/8"H x 8-5/8"D
Unit:	14-1/8"W x 12-1/8"H x 8-5/8"D 12.8 lbs.
Shipping Carton:	20-1/4"W x 13"H x 16"D 17.5 lbs.
Safety and EMI:	FCC, RoHS



Two USB Ports on the Left Side

All product and company names are trademarks, service marks or registered trademarks of their respective owners. All features and specifications are subject to change without notice.

© 2014, Printed in U.S.A.

Lit-254

SAM4S