

POWERFUL AND FLEXIBLE POS SYSTEM



The powerful and flexible FORZA POS system is a highly configurable solution that allows you to design the perfect workstation. A variety of hardware component choices provide optimum performance and reliability advantages to best fit your needs in harsh retail and foodservice environments. Add the optional vertical mount to rotate the display and add the SAM4S GCUBE thermal receipt printer to create a sleek looking, powerful kiosk terminal.

- Choice of 4th Generation Celeron J1900 or 7th Generation Core™ i3 7100U Processors
- Solid State Drive Improves Performance and Reliability
- Projected Capacitive Touch (PCT)
- Suitable for Demanding Application Software



FORZA 1500
15 inch
4:3 Aspect Ratio



FORZA 1600
15.6 inch
16:9 Aspect Ratio



Convenience / Small Grocery



Tobacco Stores / Liquor Stores



Bars / Table Service Restaurants



Quick Service / Fast Casual



Hardware, Paint or General Retail Stores



Choice of:



FORZA Series Touch Screen Terminals



Two Additional USB Ports – Choice of Touch Screen Sizes and Processors



Triple-Track Card Reader Standard



Choose From 9.7", 10.1" or 15" Optional Integrated Rear LCD Customer Displays



Easy Access to Ports – Easily Replace SSD and RAM Without Tools

Options and Upgrades


Configure your system with these easy to add options:

- Integrated Customer Display – 2 Lines x 20 Characters
- Integrated 15" or 9.7" Customer LCD (Forza 1500)
- Integrated 15.6" or 10.1" Customer LCD (Forza 1600)
- Integrated 15.6" Customer Touch LCD
- Integrated Fingerprint Reader
- Two Additional Serial Ports WiFi Module

Connectivity

- LAN
- USB (4)
- COM4 (Powered)
- Cash Drawer
- Display Port
- HDMI Option
- Line Out (Audio)
- COM1 (Powered)
- COM2 (Powered)
- COM3 (Powered)
- DC Out (12V) (For Rear LCD)
- DC In (12V)

Choose From Three Optional Port Boards



Specifications

	Celeron J1900	Core i3
Processor:	Intel Celeron J1900	Core i3 7100U
Cores / Threads:	Quad Core / 4 Threads	Dual Core / 4 Threads
Cache Memory:	2MB	3MB
Display LCD:	Choice of True Flat 15" or 15.6" LCD with LED Backlighting	
Resolution – 1500:	15.0" – 1024 x 768 / Aspect Ratio 4:3	
1600:	15.6" – 1366 x 768 / Aspect Ratio 16:9	
Brightness – 1500:	15.0" – Adjustable Up to 350 cd/m ²	
1600:	15.6" – Adjustable Up to 220 cd/m ²	
Integrated Speakers:	Integrated 2W Speaker	
Chipset (PCH):	System on Chip	
Touch:	Projected Capacitive Multi-Touch Panel (PCT)	
MCR:	Integrated USB Interface Triple Track MCR	
Mass Storage Device:	128GB 2.5" Solid State Drive	
RAID Support:	No	Yes
RAM Memory	4GB DDR3 (1 Slot) Expandable To 8GB	4GB(i3) / 8GB(i5) DDR4 (2 Slots) Expandable to 16GB
Video Memory:	Shared System Memory	
Serial Ports:	COM1 / COM2 / COM3 = DB9M With Pin 9 (0V/+5V/+12V) COM4 = RJ45 Pin 1 (0V/+5V/+12V) Voltage Selectable By BIOS	
USB Ports:	Six Total V2.0	Two V2.0 (Front) Four V3.0 (Rear)
Cash Drawer Port:	RJ12, 12V or 24V Selectable By BIOS – Maximum 2 Drawers – Supports Drawer Compulsion	
LAN Port:	RJ45 10/100/1000 Base-T (Giga LAN) RealTek RTL8111G	
Video Port:	One Display Port for Second LCD (Maximum Resolution 4096 x 2304 @ 60Hz)	
HDMI Port:	Not Applicable	One (4096 x 2304 @ 24Hz)
Audio Port:	One Line-Out	
Mic Port:	Not Applicable	
Power Supply:	60W, 12V/5A External Power Adaptor 100-240V 50-60Hz	
Current / Power Usage:	0.26A / 31.2W without Rear LCD 0.32A / 38.4W with Rear LCD	
Environment:	32° F to 95° F / 0% to 90% RH Non-Condensing	
Compatible O/S:	POSReady 7 Win 7 Pro / 8 Pro Win 10 IoT Ent. 2016 LTSB	Win 10 IoT Ent. 2016 LTSB
Dim. / Weight – Base:	11-3/8"W x 8-1/2"D x 12"H	
Unit (15" Screen):	14-5/8"W x 8-1/2"D x 17"H / 11.79 lbs.	
Shipping Carton:	19"L x 11"W x 20"H / 16 lbs.	
Safety and EMI:	KC, CE, FCC, CB, NRTL, RoHS	