

SNBC

Extraordinary
Value!

BK-L216II

8-1/2" Wide Thermal Kiosk Printer



BK-L216II shown with presenter.

The extraordinary value high-speed BK-L216II thermal kiosk printer includes advanced features and is specially suited for unattended printing applications.

- High-Speed Printing (Up to 5 Inches per Second)
- Paper Roll Up to 203mm Diameter
- Auto Paper Loading/Auto Cutter/Presenter
- Modular Design, Simple to Use and Easy to Maintain
- Flexible Paper Roll Positions (Vertical/Horizontal)
- 2D Barcode Printing
- Diagnostic and Alerts
- Programmable Presenter
- Includes Interface Cables and Power Supply



BK-L216II Thermal Kiosk Printer



Presenter



Available with Horizontal or Vertical Paper Holder



Contains Everything Necessary – Including Cables – in the Carton

Features

- Includes Interface Cables, Power Supply and CD ROM with Drivers, Utilities and User's Manual
- Specially Designed for Unattended Printing Applications
- High-Speed Printing (Up to 5 Inches per Second)
- Paper Roll Up to 203mm Diameter
- Auto Paper Loading
- Heavy Duty Rotary Auto Cutter
- Presenter
- Modular Design, Easy to Use and Maintain
- Flexible Paper Roll Positions (Vertical / Horizontal)
- 2D Barcode Printing
- Diagnostic and Alerts
- Programmable Direction Retractor

Optional Devices / Upgrades

- Horizontal Paper Holder
- Vertical Paper Holder
- 2 or 4MB Flash RAM (Factory Option)
- No Presenter

Applications

- ATM / EFT
- Coupons
- Data Communication Terminal
- DIY Design Kiosks
- Information Kiosks
- Gaming
- Gift Certificates / Gift Registry
- Healthcare
- Line Busting
- Nutrition Information
- Parking
- Personnel
- Self-Service Check Out
- Ticketing / Transportation
- Vending
- Way Finder

Specifications

	203 DPI	300 DPI
Print Method:	Direct Thermal Line Printing	
Resolution:	203 DPI x 203 DPI	300 DPI x 305 DPI
Print Width:	8-1/2" (216mm) Maximum	
Print Speed (per Second):	4-7/8" (125mm)	3-15/16" (100mm)
Print Length – Stand. Config.:	Max. 23-3/8" (594mm) / Min. 3-1/4" (82.5mm)	
Special Config.:	Max. 39-3/8" (1,000mm) / Min. 3-1/4" (82.5mm)	
Memory – SDRAM:	8MB	
FLASH:	1MB Standard / 2 or 4MB Factory Option	
Sensors:	Presenter / Retractor / Paper Out / Shutter Position / Cover Open / Paper Mark / THP Overheating Protection / Paper Near End	
Drivers:	Windows® 98 / 2000 / NT4.0 / XP / 2003 / VISTA / XP Embedded / Win7 / Linux®	
Interface:	Serial+USB / Serial+Parallel	
Bar Code – 1D:	Interleaved 2 of 5 / UPC-A / UPC-E / EAN8 / EAN13 / CODABAR / Code 39 / Code 128 / Code 93	
2D:	PDF417 / QR	
Fonts:	English / International Character Set / Codepage / Big Character Set	
Character Modification:	Rotate 0°, 90°, 180°, 270° / Underline / Emphasize / Reverse / Enlarge 1 ~ 6 Times	
Paper – Type:	Continuous Paper / Folded Paper / Marked Paper	
Paper Thickness:	0.06mm ~ 0.10mm	
Paper Width:	210mm ~ 216mm Continuous Adjustment	
Outside Diameter:	8" (203mm) Maximum	
Inside Diameter:	1" (25.4mm) or 1-15/16" (50mm)	
Paper Cutting Method:	Full Cut	
Presenter – Paper Out Speed:	15-3/4" (400mm) per Second Maximum	
Paper Retraction Speed:	15-3/4" (400mm) per Second	
Paper Presenter Mode:	Retract Paper / Hold Paper / Eject Paper (Selectable)	
Reliability – Printhead Life:	≥ 100 Km	
Cutter Life:	≥ 500,000 Cuts	
MTBF:	≥ 100,000 Hours	
Power Supply – Input:	110 ~ 240V AC, 50/60 Hz	
Output:	24 ± 10%V DC, 2.5A (Printing Duty 12.5%)	
Temperature – Operating:	40° ~ 114°F (5° ~ 45°C)	
Storage:	-40° ~ 140°F (-40° ~ 60°C)	
Humidity – Operating:	20% ~ 90% RH (Non-Condensing)	
Storage:	20% ~ 93% RH (Non-Condensing)	
Mechanism Dimensions:	8-3/8" W x 3-13/16" H x 11-9/16" D (294mm W x 97mm H x 213mm D)	
Weight:	Approx. 13.26 lbs. (6.0 kg) Without Paper Holder	
Safety and EMI:	CE / CB / UL	