

Cafeterias / Quick Service Restaurants



Dusty Environments Like Pizza & Bakeries



Theater Concessions / Ticket Booths / Box Offices



Tobacco Stores / Bars / Liquor Stores



Concession Stand / Stadium Concessions

The Look of a Tablet With Retail Hardened Reliability



The stylish HK718 Windows terminal with a 14 inch, bezel-free wide screen display is designed with projected capacitive touch and a solid state drive for optimum performance and reliability in harsh retail and food service environments. Include a 58mm or 80mm integrated printer to create a space saving, highly integrated terminal.

- Intel Bay Trail Celeron Quad Core J1900 Fanless Processor
- Slim Display and Ultra-Small Footprint Design for POS Applications Where Counter Space is at a Premium
- 14" True-Flat Wide Screen
- LED Backlighting and Projected Capacitive Touch (PCT)
- Solid State Drive for Optimum Performance and Reliability
- Optional 58mm or 80mm Integrated Thermal Receipt Printer – Modular Design For Ease of Service
- Choice of Black or White Cabinet Color
- Fully Sealed Main Board Cabinet
- Compatible with Popular Application Software





Highly Integrated POS Terminal Components

The highly integrated HK718 POS terminal offers a variety of choices including choice of black or white cabinet to fit your decor, a 58mm printer, 80mm printer or no printer and a two line by 20 character VFD or 10.1" LCD customer display. The integrated card reader is a standard feature.

Optional Integrated Printer

The compact integrated thermal receipt printer incorporates user friendly features such as drop-in paper loading.

- Choice of 58mm or 80mm thermal printers.
- Stores/prints user defined graphic logos, coupons or advertising messages.
- Printer supports both USB and serial interfaces.
- Connects to an internal USB port or to COM4 port with included cables.

VFD Customer Display

Build a strong relationship with your customer by clearly displaying each item as it is registered. Customers can easily monitor a transaction as it is entered, clearly viewing the price of each item. The display provides two lines with 20 characters per line, so that both the price and the description of the item may be displayed simultaneously. With each transaction closely monitored by the customer, the opportunity for employee theft and fraud is limited.

- VFD 2 lines of 20 columns.
- 9mm high x 5mm wide character size.
- User-defined and international character set standard.
- Supports all popular emulations.
- Connects to a dedicated internal powered COM3 port.

LCD Customer Display

The LCD customer facing display can be used to display transactional information such as pricing, product description, receipt totals, etc. Or use the display for customer-facing marketing like promotional messages and images. The customer facing LCD display will display full color graphics and video. The display receives its power from the terminal so there is no need for a separate power adaptor "brick".

- 10.1" non-touch LCD screen.
- 1280 x 800 resolution.
- 220 cd/m² brightness.
- Connects to a dedicated internal VGA port.

Terminal – Ideal for POS Applications Where Counter Space is at a Premium

Specifications

HK718

Processor:	Intel Bay Trail Celeron Quad Core J1900
Cores / Threads	Quad Core / 4 Threads
Cache Memory:	2MB
Display LCD:	True Flat 14" LCD With LED Backlighting
Resolution:	1366 x 768
Brightness:	Adjustable Up to 220 cd/m ²
Integrated Speakers:	Two Integrated 2 Watt Speakers
Chipset (PCH):	CPU Integrated
Touch:	Projected Capacitive Touch (PCT)
MCR:	Integrated USB Interface Triple Track MCR
Mass Storage Device:	128GB 2.5" Solid State Drive
RAM Memory (1 Slot):	4GB SODIMM DDR3 (1333MHz) Expandable to 8GB
Video Memory:	Shared System Memory Up To 256MB
Tilt Adjustment:	0° ~ 90°
Serial Ports – External:	COM1 / COM2 / COM5 = DB9
Internal:	COM3 For Integrated VFD COM4 For Integrated Printer
Parallel Port:	Not Applicable
USB Ports – Port Panel:	Three V2.0 / One V3.0 / One USB 24V Powered
Side:	One V2.0
Cash Drawer Port:	RJ12 (12V / 24V) Maximum 1 Drawer – Supports Open/Close
HDMI Port:	Not Applicable
LAN Port:	RJ45 10/100/1000 Base-T (Giga LAN) RealTek RTL8111F
VGA Port:	Internal Pin Port (On Main Board) For Second LCD
Audio Port:	One Line-Out
Mic Port:	Not Applicable
Power Supply:	24V/3.75A External Power Adaptor 100-240V 50-60Hz
Current / Power Usage:	0.9A / 21.6W Single Display; 3.04A / 72.96W Single Display+Printer
Environment – Operating:	41° F to 104° F / 40% to 90% RH Non-Condensing
Storage:	-4° F to 140° F / 20% to 80% RH Non-Condensing
Compatible O/S:	POSReady 7 / Windows 7 Professional / Windows 10 Professional / Windows 10 IoT Enterprise 2016 LTSB
Dim. / Weight – Overall:	13-1/2"W x 8"D x 15-1/2"H / 11 lbs.
Shipping Carton:	17"L x 13"W x 22"H / 16.4 lbs.
Safety and EMI:	FCC, Class-B / CE, Class-B / RoHS

Optional Printers

80mm

58mm

Print Method:	Thermal	Thermal
Print Width:	2-13/16" (72mm)	1-7/8" (48mm)
Paper Roll Diameter:	2-5/16" (59.5 ±0.5mm)	2-1/4" (57.5 ±0.5mm)
Maximum Print Speed:	6-11/16" (170mm) per Second	3-1/8" (80mm) per Second
Paper Width:	3-1/8" (80mm)	2-1/4" (58mm)
Paper Cutting Method:	Auto Cutter	Manual Tear
TPH Lifespan:	100 km	50 km
Temperature–Operating:	32° F to 122° F (0° C to 50° C)	
Storage:	14° F to 140° F (-10° C to 60° C)	
Humidity – Operating:	10% to 80% RH (Non-Condensing)	
Storage:	10% to 90% RH (Non-Condensing)	

The attractive, powerful HK718 Series is ideal for installations where space is at a premium and customer facing applications including retail scanning and many more like these:

- Airline Counters
- Automotive Services
- Bakery
- Box Office
- Cafeterias
- Coffee
- Concession Stands
- Convenience Stores
- Delis
- Digital Signage
- Dry Cleaners
- Financial/Banking
- Food & Drug Stores
- Food Service
- Food Truck
- Gaming
- Gift Shops
- Health Food
- Hospitality
- Ice Cream / Yogurt
- Interactive Workstations
- Liquor Stores
- Medical
- Message Stations
- Quick Service Restaurant
- Rental Stores
- Self Serve Kiosk
- Small Grocery
- Specialty Food Nutrition
- Specialty Grocery
- Streaming Video
- Table Service Restaurant
- Ticket Booths
- Tobacco & Vape Stores
- Training
- Unattended Workstations

HK718 Touch Screen Terminal



Sleek Cabinet Design




Standard Integrated Card Reader – White Cabinet Shown



Optional Integrated Rear 2 Lines by 20 Characters VFD Customer Display



Optional Integrated 10.1" LCD Customer Display



Options and Upgrades

Configure your system with these easy to add options:

- Integrated VFD Customer Display – 2 Lines x 20 Characters
- Integrated 10.1" LCD Customer Display
- Integrated 58mm or 80mm Thermal Receipt Printer
- WiFi Module

Connectivity

- A** DC In (24V)
- B** RJ11 (12V / 24V – Cash Drawer)
- C** COM1
- D** USB (Two V2.0)
- E** Powered USB (One V3.0 – 24V)
- F** USB (Two V2.0)
- G** Audio
- H** COM2
- I** COM5
- J** LAN



Plus One USB Port (V2.0) on the Right Side

Hisense

All product and company names are trademarks, service marks or registered trademarks of their respective owners. All product features are subject to change without notice.