

SNBC

Extraordinary
Value!

BTP-P36

Mobile Label Printer



The BTP-P36 is a small and lightweight mobile label printer... a prudent choice for any mobile label printing application where you need fast, on-demand printing with speeds up to 102mm (4") per second. The BTP-P36 also features a long-life Lithium-ion battery.

- Compact, Mobile Printer with LCD Display
- Easily Switch From Receipt to Label Printing
- USB+Bluetooth and USB+WiFi Interfaces
- SDK Available for Apple iOS™ and/or Android™ Compatibility
- Peeler Standard
- Includes 2600mAh Large Capacity Lithium-ion Battery
- Meets IP54 Standard for Exposure to Water and Dust
- Withstands Drop of 5 Feet (1.5 Meters)



BTP-P36 Mobile Label Printer



Compatible With Smart Devices



Water and Dust Resistance



Peeler Function Standard

Features

- Compact, Mobile Printer with LCD Display
- Easily Switch From Receipt to Label Printing
- USB+Bluetooth and USB+WiFi Interfaces
- SDK Available for Apple iOS™ and/or Android™ Compatibility
- Peeler Standard
- Includes 2600mAh Large Capacity Lithium-ion Battery
- Meets IP54 Standard for Exposure to Water and Dust
- Withstands Drop of 5 Feet (1.5 Meters)
- Includes Starter Paper Roll, Battery, External Power Adaptor and Cord, User's Manual, USB Cable and Belt Clip

Applications

- Customer Service Center
- Deliveries
- Government
- Healthcare
- Logistic
- Material Handling
- Mobile POS
- Retail
- Ticketing

Optional Devices / Upgrades

Modify or upgrade your printer with these easy-to-add options:

- Battery Charger (Single)
- Vehicle Charger
- Belt Strap
- Shoulder Strap
- Protection Case



On Screen Programming Simplifies Setup

Specifications

Print Method:	Direct Thermal
Resolution:	203 DPI
Print Width:	72mm (2.8")
Print Speed:	102mm (4") Maximum
Memory –	Flash: 16MB
	RAM: 64MB
Interpreter:	BPLZ / BPLE
Interface –	Standard: USB+Bluetooth
	Optional: WiFi
Drivers –	32 Bit: Windows® 10 / 8.1 / 8 / 7 / Server 2012 / Server 2008 / Server 2003 / XP Prof. / XP Home / 2000 Server / 2000 Prof. / Vista / POSReady 2009
	64 Bit: Windows® 10 / 8.1 / 8 / 7 / Server 2012 / Server 2008 / Server 2003 / XP / Vista
Bar Code –	1D: CODE39 / CODE93 / CODE128 / CODABAR / UPC-A / UPC-E / JAN8 (EAN8) / JAN13 (EAN13) / ITF / UPC/EAN Extensions / Planet Code / Stardard 2 of 5 / Industrial 2 of 5 / Interleaved 2 of 5 / LOGMARS / GS1 DataBar (RSS) / RSS-14 / UCC / EAN 128
	2D: PDF417 / QR Code / Maxicode / GS1 / MicroPDF417
Fonts:	Built-in Standard ASCII Character (Font A~H, P~V, 0, GS) / Built-in Scalable Character Set / User-Defined Dots or Scalable Character Set / Users Download User-Defined Character Set / English (ASCII) / United States / Britain / Japanese / Korean / Download User-Defined Fonts to the Printer
Paper –	Type: Continuous / Black Mark / Perforated Paper / Label
	Thickness: 0.06 ~ 0.16mm
	Width: 25.4 ~ 80mm (1" ~ 3.1") Maximum
	Inside Diameter: 12.5 ~ 19.1mm (1/2" ~ 3/4")
	Outside Diameter: 67mm (2-5/8") Maximum
	Paper Cutting Method: Tear-Off
Display:	LCD Screen
Alarm:	Buzzer
Battery –	Capacity: 7.4V Li-ion / 2600mAh / ATJ-BMS / Removable / Rechargeable Lithium Polymer Battery
	Charging Time: 3.5 Hours
Power Supply –	Input: AC 100 ~ 240V, 50/60 Hz Adapter Included
	Output: 12VDC±5% / 2A
Temperature –	Operating: -4° ~ 122°F (-20° ~ 50°C)
	Storage: -4° ~ 140°F (-20° ~ 60°C)
Humidity –	Operating: 10% ~ 90% RH (Non-Condensing)
	Storage: 10% ~ 90% RH (Non-Condensing)
Dimensions / Weight –	Unit: 3-3/16"Wx4-5/8"Dx7-5/16"H / 1.40 lbs. (Incl. Battery)
	Shipping Carton: 12-1/4"L x 9"W x 4"H / 2.72 lbs.
Safety and EMI:	CE / CB / FCC / UL